## 360 degree fisheye IP Network Camera



## Plug&Play Fisheye IP cameras View on iPhone/iPad and Android

The IP Camera is a 5 mega sensor/4 mega pixels camera designed for all day video surveillance on your iPhone/iPad and Android mobiles/pads. The setup is truly 1-2-3:

- 1. Connect the camera to the network
- 2. Download the app mCamView2 into your iPhone/iPad or Android
- 3. View video by the camera ID/password

The camera is a fisheye lens camera for 360 degree viewing angle. The video is corrected by the App to minimize the video distortion. You could see the video in full 360 degree view either in day time or night time with the help of 3 high power IR LEDs covering the 360 degree full range.

There are three selections for the network connection, PoE, WiFi and wired Ethernet connection. You can choose to meet your requirement best for the network connection.

The push notification is supported, so that you will get the notification from your iPhone/iPad and Android once there is any events detected through the motion detection or sound detection on the camera, even when your mobile is on sleep mode.

The SD card recording is supported, and you could playback the recorded video on your iPhone/iPad and Android. You could also do the SD card recording only when there is motion or sound detection to save the SD card storage size. The motion and sound detected recording has a 5 seconds pre-recording, so that you will always catch the critical moment.

The Time Lapse Recording is supported. The camera can do time lapse recording on the SD card and you can playback the recorded time lapse video on the mobile or tablet remotely, anywhere. This is more convenient than traditional time lapse camera which can only be played back by removing the SD card to a computer.

The ONVIF protocol is supported. You could record the video to standard NVR device. The supported ONVIF profiles are Profile S,T,G,Q.

The NAS storage is supported. You can record the video files into any normal NAS devices. And you can playback those recorded video files remotely on your mobile devices or computers.

The IP camera is ideal for securing small businesses, home offices and residences. The IP Camera is a perfect replacement of the alarm system and traditional analog CCTV camera in your house and shop.

## **Features**

- > 5 mega sensor
- ➤ 4 mega pixels for up to 1920x1920 resolution at 30 fps.
- ➤ PoE, WiFi or wired Ethernet network connection.
- ➤ Plug & play by ID/password, no IP address or DNS settings.
- ➤ H.264/H.265 video compression
- ➤ De-warping mode on App/VMS: 1O, 1P, 2P, 4R, Wall mode

- > Day and night video with 3 high power IR led.
- > SD card video recording with 5 seconds of pre-recording..
- > Time lapse video recording
- > Triple video streaming on PC, mobile and SD card recording.
- ➤ Night mode control support automatic, manual and scheduled modes.
- Connect up to 8 users simultaneously
- ➤ Bundle with free video management software CamView(Windows)/mCamView2(iOS/Android).
- ➤ Push notification on iPhone/iPad and Android for motion and sound detection.
- Email/ftp alarm message for motion and sound detection.
- > Event scheduling.
- Video recording on NAS device.
- ➤ Support ONVIF Profile S,T,G,Q
- Cloud Storage on Dropbox.
- ➤ Internal real time clock
- ➤ Watchdog function to prevent system failure.

## **Specifications**

**Models** 360 degree fisheye IP Camera

**Power** PoE or DC 12V, 1A

**Processors** RISC CPU, hardware video processing and compression.

**Network interface** Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45

PoE(Power over Ethernet) IEEE802.3af

Wireless interface 2.4G Hz WiFi

Range: 100 meters, line of sight

Image sensor RGB 5 Mega 1/2.7 inch CMOS

Automatic exposure control, automatic white balance, automatic gain control, automatic brightness control.

**Light sensitivity** 0.2 Lux (IR LED off)

0 Lux (with 10 meters IR LED on)

Automatically turn on the IR LED on low light

environment.

**IR LED** 3 high power IR LEDs.

**Lens** M12, 1.44 mm, F2.0, viewing angle- 360°,

Fixed iris. focus range: 50 cm to infinity

**Buttons** One reset button, to factory default settings

One WPS button for automatic WiFi setup

**Indicators** One LED for Internet connection status indication

One LED for Ethernet connection indication
One LED for SD card recording indication

**Video compression** H.264/H.265, high profile

Video streaming Separate frame rate/resolution/bandwidth settings

for PC and mobile.

**Video settings** Resolution: (4 mega) 1920x1920, 1536x1536, 1088x1088, 736x736

Bandwidth: 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M, 2M, 3M

bps

Frame rate: 1~5, 10, 15, 20, 25, 30 fps

**Audio** Built-in microphone for audio monitoring

Built-in 0.5W speaker for alarm and half-duplex two-way

audio.

Audio compression: G.711

**Security** Web management username/password protection

Video display ID/password protection

**Installation,** Plug & play by ID/password.

management and Video management software-CamView for video access

maintenance and multi-camera management

Firmware upgrades via FTP/SFTP/HTTP

Web browsing Built-in web server for standard web browser access

Video snapshot on any browser

**Supported protocols** IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP,

SMTP, SNTP, FTP, SFTP, DHCP, ARP, DNS, PPPoE,

etc.

Accessories (included) Bracket, power adaptor, RJ45 Ethernet cable, quick

installation guide, ID/Password card.

**Video management** Surveillance software for viewing and archiving up to 36

software cameras

Users Up to 8 simultaneous unicast users

(depends on video settings)

**Alarm and event** Events triggered by motion and sound detection

management Email/ftp alarm message

Push notification on iPhone/iPad and Android devices.

**Dimensions (HxD)** H:35mm, D:94mm(with bracket),

Weight 137g(with bracket)

**Approvals** TELEC approval for WiFi radio

Power adapter: CE, FCC, UL, EN 60950

**Operating temperature** 0-40 °C

Humidity 20 – 80% RH (non-condensing)