Full HD IP Camera



Plug&Play H.264 wireless IP cameras View on iPhone/iPad and Android

The IP Camera is a Full HD (two mega-pixel) camera designed for all day video surveillance on your iPhone/iPad and Android mobiles/pads. The setup is truly 1-2-3 :

- 1. Connect the camera to the network
- 2. Download the app mCamView into your iPhone/iPad or Android
- 3. View video by the camera ID/password

The push notification is supported, so that you will get the notification from your iPhone/iPad and Android once there is any events detected through the motion detection or sound detector on the camera, even when your mobile is on sleep mode.

The SD card recording is supported, and you could playback the recorded video on your iPhone/iPad and Android. You could also do the SD card recording only when there is motion or sound detection to save the SD card storage size. The motion and sound detected recording has a 5 seconds pre-recording, so that you will always catch the critical moment.

The Time Lapse Recording is supported. The camera can do time lapse recording on the SD card and you can playback the recorded time lapse video on the mobile or tablet remotely, anywhere. This is more convenient than traditional time lapse camera which can only be played back by removing the SD card to a computer.

The NAS and cloud storage is supported. You can record the video files into any normal NAS devices or to your Dropbox account. And you can playback those recorded video files remotely on your mobile devices or computers.

For day & night usage, there is an IR cut on the camera, IR filter is on for day and off for night. The lens is wide angle up to 140 degree.

Two-way audio is supported. You can monitor the synchronized video/audio and talk to or warn the people around the camera from your iPhone/iPad and Android once you got the push notification. There is a built-in speaker so that you could connect any high power speaker to the camera for your needs.

The WPS(WiFi Protected Setup) is supported. You could set up the WiFi connection of the camera with the router by clicking the WPS button on the camera and on the router at the same time. No more complicated WiFi configuration.

The IP camera is ideal for securing small businesses, home offices and residences. The IP Camera is a perfect replacement of the alarm system in your house and shop.

Features

- ▶ Full HD, video resolution 1920x1080 for 30 fps
- Wide angle lens up to 140 degree(horizontal)
- > Plug & play by ID/password, no IP address or DNS settings.
- ► H.264 video compression
- ➢ IR cut for day and night usage.
- Two way audio.
- SD card video recording with 5 seconds of pre-recording..
- Time lapse video recording
- ▶ WiFi with WEP and WPA/WPA2 security support.
- > WPS (WiFi Protected Setup) support.
- > Triple video streaming on PC, mobile and SD card recording.
- Night mode control support automatic, manual and scheduled modes.
- Connect up to 8 users simultaneously
- Bundle with free video management software CamView.
- Push notification on iPhone/iPad and Android for motion and sound detection.
- Email/ftp alarm message for motion and sound detection.
- Event scheduling.
- Video recording on NAS device.
- Cloud storage on Dropbox.
- Internal real time clock
- > Watchdog function to prevent system failure.

Specifications

Models	Full HD IP camera
Power	DC 5V, 1.5A
Processors Network interface	RISC CPU, hardware video processing and compression. Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45
Wireless interface	2.4G Hz WiFi Range : 100 meters, line of sight
Image sensor	RGB 2 Mega 1/2.7 inch CMOS sensor Automatic exposure control, automatic white balance, automatic gain control, automatic brightness control.
Light sensitivity	0.2 Lux (IR LED off)0 Lux (with 10 meters IR LED on)Automatically turn on the IR LED on low light environment.
Lens	M12, 2.8 mm, F1.8, viewing angle- horizontal:140°, fixed iris. focus range: 50 cm to infinity
Buttons	One reset button, to factory default settings One WPS button for automatic WiFi setup
Buttons Indicators	
	One WPS button for automatic WiFi setup One LED for Internet connection status indication One LED for Ethernet connection indication
Indicators	One WPS button for automatic WiFi setup One LED for Internet connection status indication One LED for Ethernet connection indication One LED for SD card recording indication
Indicators Video compression	One WPS button for automatic WiFi setup One LED for Internet connection status indication One LED for Ethernet connection indication One LED for SD card recording indication H.264, high profile Separate frame rate/resolution/bandwidth settings
Indicators Video compression Video streaming	One WPS button for automatic WiFi setup One LED for Internet connection status indication One LED for Ethernet connection indication One LED for SD card recording indication H.264, high profile Separate frame rate/resolution/bandwidth settings for PC and mobile. Resolution: (Full HD)1920x1080, 1280x720, 640x360 Bandwidth : 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M, 2M, 3M bps

	Video display ID/password protection
	WiFi WEP and WPA/WPA2 security mode
Installation,	Plug & play by ID/password.
management and	Video management software-CamView for video access
maintenance	and multi-camera management
	Firmware upgrades via FTP
Web browsing	Built-in web server for standard web browser access
	Video display on IE browser
	Video snapshot on any browser
Supported protocols	IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP,
	SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE, etc.
Accessories (included)	Power adaptor, RJ45 Ethernet cable, quick installation
	guide, ID/Password card.
Арр	App mCamView2 for Android and iPhone
Usam	Un to 9 simultaneous unionst users
Users	Up to 8 simultaneous unicast users
	(depends on video settings)
Alarm and event	Events triggered by motion and sound detection
management	Email/ftp alarm message
	Push notification on iPhone/iPad and Android devices.
Dimensions (HxWxD)	116 x 57 x 31 mm, bracket included
and weight	126 g, incl. camera bracket, excl. power adaptor
Approvals	EMC - CE, FCC Part 15 Subpart B Class B
	Wireless RF - CE, FCC Part 15 Subpart C
	Power supply: CE, FCC, UL, EN 60950
Operating conditions	0-50 °C
	Humidity 20 – 80% RH (non-condensing)